

PAT400 series

Portable appliance testers



- **10,000 memory storage with USB download**
- **Large 5.7" 1/4 VGA backlit full colour screen for clear results**
- **200 mA; 10 A and 25 A Bond Test with high duty cycle for repetitive testing (PAT410 - 200 mA only)**
- **Selectable PASS/FAIL limits provide instant indication of a faulty asset**
- **Optional barcode scanner and printer available to save time typing asset IDs**
- **230 V and 110 V operation for industrial, commercial and residential applications**

DESCRIPTION

The PAT400 series from Megger is a new generation of downloading portable appliance testers, fully testing portable electrical equipment to the latest edition of the Code of Practice for the In-Service Inspection and Testing of Electrical Equipment. There are 3 products in the range; the PAT410 providing a low-profile 230 V only solution without the added weight required of 110 V operation, plus a database capacity for up to 10,000 test results. The PAT420 provides the same extensive memory and downloading capability, and has the added features of 110 V operation, and also 10 A and 25 A earth bond testing. The PAT450, the top of the range, has all of these features and includes 1.5 kV and 3 kV flash testing, ideal for tool hire outlets and service workshops where flash testing is routine. All products in the range have a high duty-cycle, with the design tailored to fast testing, easy operation, and all-day use. The PAT400s feature a unique fast-re-start, so that when moving the tester from one room to another, it re-starts instantly from the same menu where it was unplugged. This is a significant timesaver, so allowing more tests per day.

USB communication provides convenient download to a standard USB memory stick, and an on-board 10,000 record memory provides interruption-free testing for improved efficiency, with a large QWERTY keypad for fast data entry. Data is directly compatible with Megger PowerSuite® software for professional certification, and all products have the option of a barcode scanner and a thermal transfer barcode label printer operating directly from the USB port. Thermal transfer labels are highly resistant, stable and easily available. The PAT420 and PAT450 have dual 230 V and 110 V operation for complete industrial, commercial and residential applications.

5 soft-keys give direct access to frequently used functions, accelerating navigation through menus and therefore increasing productivity, where time is money. Both standard and customer configurable test groups are available for fast, flexible asset testing. Tests available in the range include 250 V and 500 V insulation tests, 200 mA, 10 A and 25 A earth bond tests, differential, touch and alternative (substitute) leakage tests, operational VA tests, RCD trip-tests for portable RCDs, anti-surge and RCD protected extension leads and power cords. RCD testing is now a requirement of the UK Code of Practice.

Accessories supplied with all models include a combined earth-bond and insulation test lead, an adaptor for testing 230 V extension leads, a laptop power supply adaptor, and a carry-case for convenient product and lead storage. All instruments also include Download Manager software, to enable data to be converted into a CSV format which can be read directly on a PC using Microsoft® Excel.

Megger PowerSuite software can be purchased to compliment any PAT400, providing full databased asset management and professional electronic certificate generation, providing options for multiple clients and locations.

APPLICATION

There is a legal requirement for any landlord, employer or owner of a place of work or public place, to ensure that all electrical equipment accessible by tenants, employees or the public is maintained in a safe condition, and an acceptable method of ensuring this is by routine electrical testing. This can be performed by electrical contractors, specialist PAT testing organisations, maintenance departments, or facilities management companies.

The PAT400 range is suitable for performing portable appliance testing in locations such as hotels, public houses, schools, colleges, nurseries, shops, offices, theatres, banks, restaurants, cafés, sports and leisure facilities, cinemas, factories and hair salons etc. where high volume testing requires that accurate records may be difficult to maintain, or aided by, on-board memory and download to management software. The PAT450 is particularly suitable for use in tool-hire shops where equipment is routinely tested prior to hire, or service workshops where deep disassembly is routine, and will perform a flash test in addition to standard PAT tests.

	PAT410	PAT420	PAT450
SUPPLY			
230 V	■	■	■
110 V		■	■
Supply measurement	■	■	■
EARTH BOND/CONTINUITY			
200 mA	■	■	■
10 A		■	■
25 A	■	■	■
Bond lead null	■	■	■
INSULATION TEST			
250 V	■	■	■
500 V	■	■	■
ALTERNATIVE LEAKAGE TESTS			
Substitute	■	■	■
Differential	■	■	■
Touch current	■	■	■
OPERATION TEST			
VA Measurement	■	■	■
EXTENSION LEAD TEST			
Earth bond	■	■	■
Insulation	■	■	■
Polarity	■	■	■
Portable RCD test (230 V)	■	■	■
FLASH TEST			
1.5 kV and 3 kV			■
OTHER FEATURES			
Low-profile light weight	■		
Auto test routine	■	■	■
Manual testing	■	■	■
Fuse check	■	■	■
Colour display	■	■	■
110 V test connection		■	■
Configurable tests times	■	■	■
Selectable pass limits	■	■	■
Lead storage pouch	■	■	■
10,000 record on-board storage	■	■	■
Download to USB memory stick	■	■	■
PowerSuite compatible	■	■	■

SPECIFICATIONS

Electrical supply range

PAT410, PAT420, PAT450

230V $\pm 10\%$ $\pm 1V$ @ 50Hz $\pm 10\%$ $\pm 0.1Hz$

PAT420, PAT450

110V $\pm 10\%$ $\pm 1V$ @ 50Hz $\pm 10\%$ $\pm 0.1Hz$

Instrument accuracy cannot be guaranteed when operated on supply frequencies other than those specified above

Bond test

(10 A and 25 A) (not PAT410)

Open circuit voltage:

9 V a.c. $\pm 10\%$ $\pm 0.1 V$ (Supply: 230 V 50 Hz)

Earth bond resistance accuracy:

$\pm 5\%$ ± 3 digits (0 to 0.49 Ω)

$\pm 5\%$ ± 5 digits (0.5 to 1.99 Ω)

Earth bond resistance resolution:

10 m Ω (0 to 1.99 Ω)

Display range: 0 to 1.99 Ω

Continuity

(200mA)

Continuity test voltage:

4.0 V d.c. -0% +10%

Continuity resistance accuracy:

$\pm 5\%$ ± 3 digits (0 to 0.49 Ω)

$\pm 5\%$ ± 5 digits (0.5 to 19.99 Ω)

Continuity resistance resolution:

10 m Ω (1 to 19.99 Ω)

Display range: 0 to 19.99 Ω

Insulation test

(250 V and 500 V)

Insulation resistance accuracy (230 V):

$\pm 2\%$ ± 5 digits (0 to 19.99 M Ω)

$\pm 5\%$ ± 10 digits (20 to 99.99 M Ω)

Insulation resistance resolution:

0.01 M Ω

Display range:

0 to 99.99 M Ω

Substitute leakage current

Test voltage and frequency:

40 V a.c. $\pm 10\%$ nominal mains frequency

Leakage current accuracy:

$\pm 5\%$ ± 5 digits

Leakage current resolution:

0.01 mA

Display range:

0 to 19.99 mA

Leakage current

Test voltage and frequency:

Nominal mains supply

Differential leakage current accuracy:

$\pm 5\%$ ± 5 digits

Differential leakage current resolution:

0.01 mA

Display range:

0 to 19.99 mA

Touch current test

Test voltage and frequency:

Nominal mains supply

Touch current accuracy:

$\pm 5\%$ ± 5 digits

Touch current resolution:

0.01 mA

Display range: 0.00 to 10 mA

Operational test

Test voltage and frequency:

Nominal mains supply

VA accuracy:

$\pm 5\%$ ± 10 digits (0 - 99 VA)

$\pm 5\%$ ± 50 digits (100 VA - 999 VA)

$\pm 5\%$ ± 100 digits (1000 VA - 3700 VA)

Resolution:

1 VA (0 to 3700 VA)

Display range:

0 to 3.99 VA

Ext Lead Test

Tests performed:

Bond, insulation and polarity

Polarity test voltage:

12 V dc

Polarity checks:

Lead OK

Live neutral S/C

Live neutral reverse

Live/neutral O/C

Flash test

Flash test voltage:

1500 V a.c. nominal for Class 1

3000 V a.c. nominal for Class 2

Flash test current:

<3.5 mA short circuit @ 253 V primary supply voltage

Flash test breakdown current accuracy:

$\pm 5\%$ ± 5 digits

Flash test breakdown current resolution:

0.01 mA

Display range:

0.00 to 3.0 mA

RCD tests

Test voltage and frequency:

230 V 50 Hz

Test current accuracy:

-8% to -2% (1/2 x I)

+2% to +8% (1 x I, 5 x I)

Trip time accuracy:

$\pm 1\%$ ± 5 digits

Trip time resolution:

0.1 ms

Display range:

0 to 1999 ms (1/2 x I)

0 to 300 ms (1 x I)

0 to 40 ms (5 x I)

Fuse Test

Test voltage:

3.3 V

Warning:

Audible beep if fuse is OK

Operating temperature range and humidity

-10 to +50 °C

90% RH @ -10 to +30 °C

75% RH @ +30 to +50 °C

Storage temperature range and humidity

-20 to +60 °C

90% RH @ -10 to +30 °C

75% RH @ +30 to +50 °C

Maximum altitude 2000 m

IP rating IP40

Dimensions

PAT410 145 (H) x 255 (B) x 320 (L)

PAT420 180 (H) x 255 (B) x 320 (L)

PAT450 180 (H) x 255 (B) x 320 (L)

Dimensions (instrument and packaging) 210 mm (H) x 280 mm (W) x 390 mm (L)

Weight

PAT410 (with packaging) 2,7 kg (3,2 kg)

PAT420 (with packaging) 4.4 kg (4.9 kg)

PAT450 (mit Verpackung) 5,0 kg (5,5 kg)

Over-voltage safety category IEC 61010-1: CAT II 300 V

EMC IEC 61326-1: 2006
IEC 61326-2-2: 2005

ORDERING INFORMATION

Description	Order Code	Description	Order Code
PAT410-UK	1000-745		
PAT420-UK	1000-752		
PAT450-UK	1000-755		
Included accessories		Optional accessories	
Printed quick start guide		UKAS certificate	1001-285
Full user guide on CD		110 V Extension lead adaptor	6220-639
Calibration Certificate	1001-284	110 V mains lead adaptor	1000-766
Continuity/earth bond lead	1001-233	415 V adaptor lead (4-pin) to BS1363 (16 A)	1000-767
Extension lead adaptor BS1363	1001-234	415 V adaptor lead (5 pin) to BS1363 (16 A)	1000-770
Flash test lead	1007-165	Barcode reader, USB	1001-047
Carry case with lead/document pouch	2000-962	Barcode Label Printer (Brother P700) (USB)	1005-423
Plug adaptor IEC C6 - C13	1001-232	USB cable	1004-610
		Barcode printer label refills (cartridge)	90001-010
		Appliance bar-code labels (1-1000)	6121-483
		Roll of 1000 FAIL test labels	1001-227
		Roll of 1000 PASS test labels	1000-971
		PAT accessory pouch	2001-044
		PAT test certificate book	1001-299
		Screen protector (2)	1002-572